Product data sheet Characteristics

QDP22200TM

PowerPact Q - molded case circuit breaker - 2pole - 25 kA - 240 V - 200 A

Product availability: Stock - Normally stocked in distribution facility





Main

| Product or component type | Circuit breaker |
|---------------------------|--|
| Range of product | PowerPact Q |
| Trip unit technology | Thermal-magnetic |
| Provided equipment | Lug at OFF end Stud with nut and washer at ON end |

Complementary

| Line Detect Comment | 200 4 | · · · · · · · · · · · · · · · · · · · |
|---|---|---------------------------------------|
| Line Rated Current | 200 A | |
| System Voltage | 240 V AC | : |
| Number of poles | 2 | |
| Breaking capacity | 25 kA 240 V AC | |
| [lcs] rated service short-circuit breaking capacity | 50 % | |
| Breaking capacity code | D | |
| Mounting mode | Unit mount | : |
| Electrical connection | Lugs on load: AWG 4300 kcmil (aluminium/copper) Terminal nut on line | , |
| Magnetic hold current | 1200 A | |
| Magnetic tripping current | 2400 A | |

Environment

| | | 5 |
|------------------------|-----------|--------------|
| Product certifications | CSA | . <u>v</u> |
| r reduct continuations | IEC | |
| | | <u></u> |
| | UL listed | - |
| | | <u></u> |

Ordering and shipping details

| rasing and simplify a stand | | |
|-----------------------------|-----------------------------------|---|
| Category | 00024 - Q2 & QE METERING BREAKERS | ٥ |

| Discount Schedule | DE2A | |
|-----------------------|-------------------|--|
| GTIN | 00785901672487 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 3.260000000000002 | |
| Returnability | Υ | |
| Country of origin | MX | |

Offer Sustainability

| Sustainable offer status | Not Green Premium product |
|--------------------------|-----------------------------|
| RoHS (date code: YYWW) | Will be compliant on 4Q2016 |
| | Will be compliant on 4Q2016 |

Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|
| | |