

QO1520

QO Tandem Mini Circuit Breaker 15/20A 1P 120/240V 10kA Plug-in Mount

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|-----------------------------|---------------------------|
| Product or component type | Miniature circuit-breaker |
| Range of product | QO |
| Line Rated Current | 15 A 20 A |
| System Voltage | 120/240 V AC |
| Mounting mode | Plug-in |
| Poles description | 1P |
| Circuit breaker type | Tandem |
| Circuit breaker application | HACR rated |
| Electrical connection | Box lugs |

Complementary

| | |
|---------------------------|--------------------------------------|
| Breaking capacity | 10 kA at: 120/240 V AC |
| Number of spaces required | 1 |
| AWG gauge | AWG 14...AWG 8 (copper or aluminium) |

Environment

| | |
|---------------------------------------|------------------|
| Product certifications | UL listed CSA |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 00181 - REPLCMNT TANDEMS - DO NOT NEGOTIATE |
| Discount Schedule | DE2A |
| GTIN | 00785901400929 |
| Nbr. of units in pkg. | 10 |

| | |
|---------------------|---------------------|
| Package weight(Lbs) | 0.32000000000000001 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|