


Product availability : Stock - Normally stocked in distribution facility



### Main

Range of product	Altivar
Product or component type	Encoder interface card
Range compatibility	Altivar Lift Altivar 71Q Altivar 71 Altivar 61Q Altivar 61
Discrete output type	Push-pull
[Us] rated supply voltage	24 V DC (voltage limits: 20...30 V)
Number of pulses per revolution	<= 10000 ATV71H.....383 <= 5000 all ATV61 drives <= 5000 ATV71H...M3 <= 5000 ATV71H...M3X <= 5000 ATV71H...N4

### Complementary

Supply current	<= 0.175 A
Protection type	Overload protection Short-circuit protection
Max cable distance between devices	500 m
Maximum operating frequency	300 kHz
Input signal	A B Compliment of A Compliment of B/AB/A
Input impedance	1000 Ohm
Voltage state 0 guaranteed	<= 1.5 V
Voltage state 1 guaranteed	> 11.5...< 25 V
Electrical connection	Terminal, connection capacity: 0.2 mm <sup>2</sup> (AWG 24) 500 m cable length (encoder 100 mA) at 14 V

Ordering and shipping details

Category	22135 - ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	00785901526919
Nbr. of units in pkg.	1
Package weight(Lbs)	0.35999999999999999
Returnability	Y
Country of origin	ID

Contractual warranty

Warranty period	18 months
-----------------	-----------