

# Product data sheet

## Characteristics

# XACB9222

booted head for pushbutton XAC-B - black - 16 mm, -40..+70 °C

Product availability : Stock - Normally stocked in distribution facility



### Main

Range of product	Harmony XAC
Product or component type	Head for push-button
Component name	XACB
Marking	Unmarked
Operator additional information	Booted
Operating travel	0.63 in (16 mm)
Cap/Operator or lens colour	Black
Product compatibility	XESD1291 XESD1191 XESD1281 XESD1181
Sale per indivisible quantity	10

### Complementary

Product weight	0.01 lb(US) (0.005 kg)
----------------	------------------------

### Environment

Standards	IEC 60947-5-1 CSA C22.2 No 14 EN 60947-5-1
Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Electrical shock protection class	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 50102

Ordering and shipping details

Category	22473 - PUSHBUTTON, PENDANTS
Discount Schedule	CS2
GTIN	00785901644729
Nbr. of units in pkg.	10
Package weight(Lbs)	0.02
Returnability	Y
Country of origin	CZ

Contractual warranty

Warranty period	18 months
-----------------	-----------