


## FLAT (SAE) WASHER - GALVANIZED STEEL

The following Specification Sheet applies to all **Flat (SAE) Washers – Galvanized Steel** in our **JSW series**.



SAE Flat Washers								
Nominal Washer Size	ID			OD			TH	
	Inside Diameter			Outside Diameter			Thickness	
	Basic	Tolerance		Basic	Tolerance		Max.	Min.
		Plus	Minus	Dasic	Plus	Minus	iviax.	IVIIII.
1/4	.281	.015	.005	.625	.015	.005	.080	.051
5/16	.344	.015	.005	.688	.015	.007	.080	.051
3/8	.406	.015	.005	.812	.015	.007	.080	.051
1/2	.531	.015	.005	1.062	.030	.007	.121	.074
5/8	.656	.030	.007	1.312	.030	.007	.121	.074
3/4	.812	.030	.007	1.469	.030	.007	.160	.108

## Specification Requirements:

Dimensions: ASME B18.21.1, Type A, Narrow Plain Washers

• Material: Low Carbon Steel

• Finish: Hot Dip Galvanize per ASTM A153/A153M or ASTM F2329/F2329M

## **Metallics**

229 Cross Street Bristol, CT 06010 www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272 Fax: 860 584-1008 Toll Free Fax: 800 831-9358