



► Model RSL-LMM

# Radiant Multi-Pattern Light Module



RSL-LMM offers a multi-pattern LED light with high optical performance. Its modular design and compound functionality make this module ideal for applications where gaining attention is required.

RSL-LMM is capable of producing four integrated light effects: double flash, triple flash, strobe effect and random. The random pattern consists of an uneven flashing pattern, increasing the ability to catch attention.

Pattern selection in the individual light modules allows each light module in your configuration to activate a different flash pattern.

## FEATURES

- Modular design allows for up to 7 light modules: 6 light modules & 1 sound module (1 channel) or 5 light modules & 1 sound module (2 channels)
- Four integrated flash patterns selectable via DIP switch
- Compatible with 12-24VAC/DC or 120-240VAC\*
- PLC compatible
- Indoor/outdoor use
- Type 4X, IP65 enclosure when installed with both gaskets included with each module
- IP69K compliant when installed with both gaskets included on each module
- CE Certified
- UL and cUL Listed

\*Voltage dependent on selected wiring module



Wiring Modules

MODEL	MAXIMUM OPERATING CURRENT* (mA)			
	24VDC	24VAC	120VAC	240VAC
RSL-LMM				
<b>RSL-WML/RSL-WMH</b>	60	100	35	25

\* Maximum operating current is for one module. For multiple modules the current will have to be added throughout the configuration to get the total maximum operating current.

