

Photocontrols - Shutter Style



Fixed Base



Swivel Base

- ▶ Polycarbonate Weatherproof Housing
- ▶ Adjustable Slide Bar Allows Field Adjustments
- ▶ 30-60 Second Time Delay
- ▶ Contact Position: Normally Closed
- ▶ SPST
- ▶ Temp Rate: -40°F to 158°F
- ▶ Relative Humidity: 96%
- ▶ Power Consumption: 1.5 Watts Average
- ▶ 6 Color Coded Leads
- ▶ 1/2" Threaded Base with Rubber Gasket & Zinc Locknut

Fixed Base

Cat. No.	Voltage	Tungsten Rating	Ballast Rating	Case Qty
39010	120V	2000W	2000VA	100
39012	208-277V	2000W	2000VA	100

Swivel Base

Cat. No.	Voltage	Tungsten Rating	Ballast Rating	Case Qty
39020	120V	2000W	2000VA	100
39022	208-277V	2000W	2000VA	100

Photocontrols - Shutter Style - Spec Grade



- ▶ Die Cast Aluminum Vandal Resistant Housing
- ▶ 1" Extra Wide Light Sensor for Increased Accuracy
- ▶ Adjustable Slide Bar Allows Field Adjustments
- ▶ 30-60 Second Time Delay
- ▶ Contact Position: Normally Closed
- ▶ SPST
- ▶ Temp Rate: -40°F to 158°F
- ▶ Relative Humidity: 96%
- ▶ Power Consumption: 1.5 Watts Average
- ▶ 6 Color Coded Leads
- ▶ 1/2" Threaded Swivel Base with Rubber Gasket & Zinc

Fixed Base

Cat. No.	Voltage	Tungsten Rating	Ballast Rating	Light Sensor	Case Qty
39011	120V	3000W	3000VA	1"	50
39013	208-277V	3000W	3000VA	1"	50

Locking Style Receptacles



Fig 1 - Fixture Mount



Fig 2 - Bracket Mount

- ▶ Phenolic Socket
- ▶ Brass Contacts
- ▶ ABS Waterproof Back Cover
- ▶ 1/2" Conduit with Zinc Alloy Locknut
- ▶ Temp Rate: -40°F to 176°F
- ▶ Relative Humidity : 96%

Cat. No.	Fig	Mount	Voltage	Amps	Case Qty
39070	1	Fixture	0-480V	15	100
39072	2	Aluminum Bracket	0-480V	15	100