



Product Description

Extreme pressure MOLY-GRAPH Multi-Purpose Grease is the best general purpose grease for a wide range of applications. It offers an excellent mechanical and shear stable Lithium 12 Hydroxy Protection of "moly" and graphite. Timken load of 40 lbs.

Product Specifications

Applications	Automotive applications, backing plates, ball joints, chassis points, construction ball & roller bearings, idler bearings, industrial applications, mining applications, pillow block bearings, sprocket bearings, U-joints, water pumps, wheel bearings
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	E. P. Multi-Purpose Lithium Grease
Net Fill	14 Wt Oz
UPC Code	072213333008
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	10 lbs
I 2 of 5 Code	30072213333009
Appearance	Grey Semi-Solid to Solid Grease
Odor	Faint Petroleum
Base Type	Lithium-12
Flashpoint	>400°F
Flammability	Non-flammable
Specific Gravity	0.9 at 60°F
NLGI Grade	2
Timken OK Load [Lbs.]	45 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)
Working Temp	-25 to 250°F
4 Ball EP	250 KG Weld,30 LWI (Min)
4 Ball Wear	0.6 mm typical
Drop Point	350°F
Elastomer Compatibility	0 to 40% vol ; 0 to 15 hard
Leakage	10g Max
Low Temp Torque	15.5 Max
Oil Separation	<10%
Oxidation Stability	5
Pour Point	0°F
ISO Viscosity Grade	150
Water Washout	<15%
Worked Penetration	265 to 295
Propellant	None
NSF Registered	No
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0.2
VOC g/L (Federal)	1.8
VOC Lbs./Gal. (Federal)	0.015
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.