



**Description** 12V 35W 38 Deg. Flood MR16 GU5.3 Base  
**Ordering Code** 15051  
**UNSPSC Code** 39101601

**Specifications**

<b>Voltage Rating</b>	12
<b>Watts</b>	35
<b>Amps</b>	2.92
<b>Base Type</b>	GU5.3
<b>Bulb Type</b>	MR16
<b>Filament</b>	C-8
<b>MOL in/mm</b>	1.81/46.0
<b>MOD in/mm</b>	2.00/50.8
<b>Approx Initial Max Beam CP</b>	900
<b>CT deg K</b>	2950
<b>Beam Angle</b>	38
<b>Beam Description</b>	Flood
<b>Rated Life</b>	4,000
<b>Common Code</b>	Q35MR16/FL
<b>Burning Position</b>	Any
<b>Special Desc</b>	Dichroic Reflector
<b>Type Use</b>	Display 38

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335