



NUVO SERIES TWO 6.5" ANGLED IN-CEILING SPEAKERS

NV-2IC6-ANG |

FEATURES & BENEFITS

The NUVO Angled In-Ceiling speakers are designed to perform and look great. This 6.5" model has silk dome tweeters and poly woofers, and is finished beautifully with their completely rimless, magnetic grill. They also offer quick and secure installation by utilizing three dog legs, instead of the usual four, and includes pivoting tweeters. These tweeters are connected to a unique tweeter bridge that maximizes sound quality, looks great, and serves as a handle to hold the speaker by during installation. The NV-2IC6-ANG serves equally well for in-ceiling theater installation, as it does for targeted two channel audio installations. These speakers have a fifteen degree baffle that angles the woofer and tweeter towards the seating positions of the listener.



- 8 ohm rated
- Angled fifteen degree baffle with Pivoting tweeter
- Three dog leg design for easy installation
- Magnetic rimless and paintable grill
- Pivoting tweeter
- Unique tweeter bridge that also doubles as an installation handle
- Lifetime Warranty

SPECIFICATIONS

Wattage: 50W rms
Maximum Wattage: 100W Peak
Woofer Diameter: 6.5" (165mm)
Woofer Composition: Poly
Surround Material: Rubber
Number of Woofers: 1
Tweeter Size: 0.5" diameter (13mm)
Tweeter Composition: Silk Dome
Number of Tweeters: 1

Decibels: 86 dB
Sensitivity: 86 dB (1 watt/meter)
Impedance: 8Ω
Frequency Response: 60 Hz - 20 KHz (+/- 3 dB)
Cutoff Frequency: 4 KHz

GENERAL INFO

Color: White
Type: Indoor, In-Ceiling, Round
Special Features: Magnetic thin bezel, poly woofer, UFLC soft dome tweeter, steel powder coated grill

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

DIMENSIONS

Depth (Metric): 116mm
Depth (US): 4.57"
Height (Metric): 230mm
Height (US): 9.06"
Length (Metric): 117mm
Length (US): 4.61"
Width (Metric): 230mm
Width (US): 9.06"

TECHNICAL INFORMATION

Frequency Response: 60 Hz - 20 KHz (+/- 3 dB)
Material: ABS frames and stamped metal baskets
Mounting: Cutout Round: 8.07" (205mm)
NEMA Rating: 5WD Wiring Devices, Building Systems
Speaker Impedance Load: 8Ω
Tweeter Type: Silk Dome
Watts: 50W RMS
Woofer Type: Poly